



Johnston Farm Equipment Ltd.

Athlone Road, Longford, Ireland

Tel: (043) 33 46837 / 33 41951. Fax: (043) 33 45877

E-Mail: info@johnston.ie Web: www.johnston.ie

PADDOCK HARROWS



Paddock Harrows are designed to cover all applications from small holdings to sports arenas and equestrian centres and are manufactured from 7/16" diameter high carbon steel which ensures that the harrow is extremely strong with high resistance to wear.

Trailed Harrows are available in widths from 4'-0" up to a maximum of 8'-0" with a depth of 5'-0" and are designed for towing behind ATV's, compact tractors, quad bikes and ride-on mowers.



Mounted Harrows are available in widths from 4'-0" to 12'-0" with a depth of 5'-0" and are designed for use with compact tractors and ATV's. Harrows over 6'-0" wide are manual folding.

These harrows can be supplied complete with drawbars and frames or sections can be supplied separately if required.

Paddock Harrow Specifications

			TRAILED Working Widths and Weight (Kg) Complete									
Type	Depth	Tine Size	3'-3"	4'-0"	5'-0"	6'-0"	8'-0"	10'-0"	12'-0"	14'-0"	16'-0"	20'-0"
Paddock	5'-0"	7/16" Dia x 2 1/2	-	40	48	57	81	-	-	-	-	-
			MOUNTED Working Widths and Weight (Kg) Complete									
Type	Depth	Tine Size	3'-3"	4'-0"	5'-0"	6'-0"	8'-0"	10'-0"	12'-0"	14'-0"	16'-0"	20'-0"
Paddock	5'-0"	7/16" Dia x 2 1/2	-	95	-	125	143	-	190	-	-	-