



Johnston Farm Equipment Ltd.

Athlone Road, Longford, Ireland

Tel: (043) 33 46837 / 33 41951. Fax: (043) 33 45877

E-Mail: info@johnston.ie Web: www.johnston.ie

TRAILED HARROWS

Trailed chain harrows include, Heavy Grass, Superflex, Chain & Spike, Concord, Ranger and Paddock. They are designed to be towed behind tractors or other suitable vehicle.

Trailed chain harrows are available in widths from 4'-0" through to 20'-0". They can be supplied complete with drawbar or sections only.

Universal drawbars are manufactured from heavy duty steel tube complete with chain draft. The drawbars are fitted with a steel attachment bar with welded spacers to allow universal attachment points and are designed to pull the harrows at the correct angle so that the ground is completely covered.



Trailed Harrow Specifications

Type	Depth	Tine Size	Working Widths and Weight (Kg) Complete									
			3'-3"	4'-0"	5'-0"	6'-0"	8'-0"	10'-0"	12'-0"	14'-0"	16'-0"	20'-0"
Mini Medium Grass	5'-0"	7/16" Dia x 2 1/2"	-	31	36	44	60	-	-	-	-	-
Heavy Grass	7'-6"	1/2" Dia x 2 1/2"	-	60	-	105	130	160	185	225	255	320
Mini Heavy Grass	6'-0"	1/2" Dia x 2 1/2"	-	48	-	75	-	-	-	-	-	-
Superflex	7'-6"	1/2" Dia x 2 1/2"	31	-	-	-	-	-	-	-	-	-
Concord	7'-6"	1/2" Dia x 3 1/2"	-	68	-	110	145	180	207	250	290	365
Chain & Spike	7'-6"	1/2" Dia x 3 1/2"	-	75	-	121	140	175	210	245	277	346
Paddock	5'-0"	7/16" Dia x 2 1/2"	-	40	48	57	81	-	-	-	-	-
Ranger	6'-0"	5/8" Dia x 4 1/2"	-	82	-	125	-	-	-	-	-	-



Johnston Farm Equipment Ltd.

Athlone Road, Longford, Ireland

Tel: (043) 33 46837 / 33 41951. Fax: (043) 33 45877

E-Mail: info@johnston.ie Web: www.johnston.ie

SUPERFLEX HARROWS

Our Superflex chain harrow section is designed to be compatible with Parmiter frames and drawbars. Manufactured from 1/2" diameter high quality carbon steel ensuring that the harrow is extremely strong with a high resistance to wear.

The section is supplied in 3'-3" widths x 7'-6" long.



Trailed Harrow Drawbar Attachment



Universal Drawbars are manufactured from heavy duty steel tube complete with chain draft. The drawbars are strengthened by a steel attachment bar with welded spacers to allow universal attachment points.